

DCN-CON Cententus Basic

www.boschsecurity.com



BOSCH

Invented for life



- ▶ Low susceptibility to mobile phones
- ▶ Compact, attractive delegate unit
- ▶ Built-in fold-away flat-panel loudspeaker
- ▶ Five voting buttons
- ▶ Cable connections located underneath the unit

The DCN-CON is the standard delegate conference unit that enables delegates to speak, register a request-to-speak, register a response request, listen to the speaker and vote. It has low susceptibility to interference from mobile phones. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately). The flat-panel loudspeaker offers superior acoustics with minimal feedback, thus increasing intelligibility. It is automatically muted when the microphone is activated. When the unit is not being used, the loudspeaker panel conveniently folds down. There are five voting buttons for all kind of voting. An external contact is available to connect external fingerprint readers.

Functions

Controls and indicators

- Built-in, fold-away, flat-panel loudspeaker, automatically muted if the microphone is on
- Microphone 'on/off' or 'request-to-speak' button
- 'Microphone on' indicator at the top of the loudspeaker
- Tri-color indicator above the microphone button:
 - Red 'Microphone on' indicator
 - Green 'Request-to-speak' confirmation indicator

- Yellow 'VIP' indicator. 'VIP' LED is lit when the delegate unit is part of the notebook, which is only available when PC control software is used
- Five voting buttons with yellow LED confirmation indicators These can be used to register:
 - PRESENT, YES (+), NO (-), ABSTAIN (X), (parliamentary voting)
 - Numerals: 1 to 5 (multiple choice or opinion polls)
 - Rating scale: - -, -, 0, +, ++ (audience response)

Connections

- Socket for pluggable microphone
- 2 m (78.7 in) cable terminated in a molded six-pole circular connector
- Six-pole circular connector for loop-through connections
- Eight-pole modular jack connector for Intercom Handset LBB 3555/00 and external present and Fraud contact e.g. a fingerprint reader

Certifications and Approvals

Region	Certification
Europe	CE

Technical Specifications

Mechanical

Mounting	Tabletop (portable or fixed mounting) and flush mounting
Dimensions (H x W x D)	(without microphone)
Tabletop	50 x 275 x 155 mm (2.0 x 10.8 x 6.1 in)
Flush mounted	30 x 275 x 155 mm (1.2 x 10.8 x 6.1 in)
Weight	1.4 kg (3.1 lb)
Color top	Charcoal (PH 10736) with silver (RAL 9022) panel
Color base	Charcoal (PH 10736)

Ordering Information

DCN-CON Concentus Basic

pluggable microphone, voting, microphone to be ordered separately

Order number **DCN-CON**

Accessories

DCN-MICS Pluggable Short Microphone

length 310 mm (12.2 inch), silver

Order number **DCN-MICS**

DCN-MICL Pluggable Long Microphone

length 480 mm (18.9 inch), silver

Order number **DCN-MICL**

Represented by:

Americas:

Bosch Communications Systems
12000 Portland Avenue South
Burnsville, Minnesota 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone: +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com